



LITE-SOIL

ALL in ONE: Air-Soil-Water

Tender text all products, overview:

TECHNICAL CHARACTERISTICS

Our products are made of long-time proven nonwovens, which are optimized for any type of soil. Up to 90% of the volume consists of interconnected air pores, which can store water and redistribute it by capillary action. All the water is thus immediately available to plants. Our products are available in 3 different materials:

		weight	thickness
BIO1	WOOD FIBER (100% cellulose fibers) 100% biodegradable after about 1-2 years	330 g/m ²	4 mm
		600 g/m ²	6 mm
BIO5	PLA (70% PLA + 30% cellulose fibers) 100% biodegradable/compostable after approx. 5-10 years	500 g/m ²	6 mm
PP	PP (100% polypropylene fibers) durable, reusable and sustainable	360 g/m ²	3 mm
		600 g/m ²	5 mm

Standard products overview

			Bio1		Bio5		PP	
			4 mm	6 mm	6 mm	3 mm	5 mm	
LITE-STRIPS								
	Units	Weight in Kg: Bio1/Bio5/PP						
70 x 12 mm	1 m ³ BB	50/45/50		X	X			X
70 x 12 mm	5 x 50 l Box	12/11/12		X	X			X
70 x 12 mm	250 l Box	12/11/12		X	X			X
70 x 12 mm	60 l Box	3,8/3,5/3,8		X	X			X
LITE-CUBES								
12 x 12 mm	1 m ³ BB	60/55/60		X	X			X
12 x 12 mm	250 l Box	15/13/15		X	X			X
LITE-NET *								
LITE-NET Tree			L - For root balls up to max. Ø 60/65 cm XL - For root balls from approx. Ø 60 cm					
L: 1,5 x 0,8 m	90 pcs. Box	23/19/23		X	X			X
L: 1,5 x 0,8 m	18 (6x3) pcs. Box	4,8/4,1/4,8		X	X			X
L: 1,5 x 0,8 m	20 pcs. Box	5,2/4,5/5,2		X	X			X
XL: 1,75 x 1,6 m	45 pcs. Box	19/16/19		X	X			X
XL: 1,75 x 1,6 m	8 pcs. Box	4/4,8			X			X
XL: 1,75 x 1,6 m	8 (4x2) pcs. Box	4/4,8			X			X
KOMBI IRRIGATION BAG (IB) + LITE-NET TREE (LNT)								
A. IB + LNT Bio5 L	30+30 pcs. Box	21+7,2			X			
B. IB + LNT Bio5 L + XL	30+(30+30) pcs. Box	21+19,8			X			
LITE-NET Slope (Roll C14 = meshes Ø 9 cm)								
350: 3,5 x 14,3 m	50 m ²	7/12/10	X	X	X			
520: 5,2 x 14,3 m	75 m ²	10/17/14	X	X	X			
LITE-NET Standard (Roll C20 = meshes Ø 13 cm)								
175: 1,75 x 16,3 m	28 m ²	6/5/6		X	X			X
175: 1,75 x 16,3 m	3 pcs. á 28 m ²	18/14/18		X	X			X
350: 3,5 x 16,3 m	57 m ²	10/11			X			X
520: 5,2 x 16,3 m	85 m ²	14/16			X			X
520 XL: 5,2 x 25,9 m	275 m ²	300						X
BLUELITE-NET COMPONENTS								
BLUELITE COVER	16 pcs. á 25 m	25					X	
BLUELITE TUBE**	100 m	14					X	
BLUELITE RING	10 pcs. á Ø 50 cm	4					X	
BLUELITE-NET SYSTEM:			LITE-NET Standard Roll PP + BLUELITE TUBE					
BLUELITE NET SYSTEM**	55 m ²	25						X
BLUELITE NET SYSTEM**	85 m ²	38						X
BLUELITE NET SYSTEM**	1200 m ²							X
LITE-ROOTPROTECT								
Root bandage	8 pcs. á 0,1 x 8 m	3	X					
Root bandage	16 pcs. á 0,1 x 8 m	6	X					
Root curtain M	0,8 x 20 m	5	X					
Root curtain M	0,8 x 100 m	236	X					
Root curtain L	1,2 x 20 m	7	X					
Root curtain L	1,2 x 100 m	268	X					
SALFIX-MAT								
4m ²	2 Stk. 2 x 1 m							8 mm

** Drip irrigation tube:

A. Rivulus D5000

B. Rainbird XFD

C. Rainbird XFS

* Specifications are maximum sizes. Recommendation: For optimal results and easier installation, reduce the laying width e.g., instead of 5,2 m only 4 - 4,5 m (area reduction approx. 10 - 15%).

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

Tender text all products:

1. **LITE-STRIPS**: Water storage and aeration close to the roots in strip form
2. **LITE-NET** rolls: Water storage net and water distribution net
3. **LITE-NET Tree**: Pre-assembled vegetation and distribution net for trees
4. **LITE-ROOTPROTECT**: Root protection nonwoven for trees on construction sites
5. **BLUELITE-NET**: Water-saving underground irrigation
6. **LITE-CUBES**: Water storage cubes for special applications
7. **BLUELITE-RING**: Ready-made for trees
8. **SALFIX-MAT**: The filter mat for protection against road salt

1. LITE-STRIPS:

As substrate improvement and near-root water storage for lawns, athletic fields, green roofs, slopes, trees, vegetation aid for turf, large tree transplantations, plant pots and raised planting beds in 3 material variants:



Bio1



Bio5



PP

1.1 LITE-STRIPS Bio1:

Water storage nonwoven in strip form (approx. 70/12/6 mm) to be mixed into the soil as irrigation close to the roots and vegetation aid as well as to improve substrate permeability and against compaction, cut from 100 % **biodegradable** wood-based cellulose needle non-woven (approx. 600 g/m², thickness approx. 6 mm, pore content/water storage ≥ 85 %, water storage capacity up to approx. 10 l/kg, **degradation time approx. 1-2 years**).

Mixing ratio for lawns approx. 0.5 to 1.0 l per m², for raised planting beds 5-10 l per m², approx. 10-20 l per tree pit, approx. 3 % vol. for large volumes, 5 - 10 % of vol. for smaller plant pots.

Delivery form: 1 m³ (ca. 50 kg), 5 x 50l, 250l or 60l.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

1.2 LITE-STRIPS Bio5:

Water storage nonwoven in strip form (approx. 70/12/6 mm) for mixing into the soil as irrigation close to the roots and vegetation aid as well as for improving substrate permeability and against compaction, cut from 100 % **biodegradable/compostable** PLA needle nonwoven (approx. 70% PLA + 30 % cellulose, approx. 500 g/m², thickness approx. 6 mm, pore content/water storage ≥ 85%, water storage capacity up to approx. 10 l/kg, **degradation time approx. 5-10 years**).

Mixing ratio for lawns approx. 0.5 to 1.0 l per m², for roof greening approx. 1.0 – 2.0 l/m², for raised planting beds 5-10 l per m², approx. 10-20 l per tree pit, approx. 3 % vol. for large volumes, 5 - 10 % of vol. for smaller plant pots.

Delivery form: 1 m³ (ca. 45 kg), 5 x 50l, 250l or 60l.

1.3 LITE-STRIPS PP:

Water storage nonwoven in strip form (approx. 70/12/5 mm) for mixing into the soil as irrigation close to the roots and vegetation aid as well as for improving substrate permeability and against compaction, cut from **durable** PP needle-punched nonwoven (approx. 600 g/m², UV stabilized, thickness approx. 5 mm, pore content/water storage ≥ 85%, water storage capacity up to approx. 10 l/kg, pore opening width < 80 µm (EN ISO 12956), maximum tensile strength ≥ 40 kN/m (EN ISO 10319)).

Mixing ratio, for lawns approx. 0.5 to 1.0 l per m², for green roofs approx. 1.0 - 2.0 l/m², for raised planting beds 5-10 l per m², approx. 10-20 l per tree pit, approx. 3 % vol. for large volumes, 5 - 10 % of vol. for smaller plant pots.

Delivery form: 1 m³ (ca. 50 kg), 5 x 50l, 250l or 60l.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL


ALL in ONE: Air-Soil-Water

2. LITE-NET rolls:

For underground air and water supply in 3 sizes each,
2 mesh sizes, 3 materials and 2 thicknesses



Bio1



Bio5



PP

Designation declaration, e.g. for Bio5 520 C20/6:

Bio5: there are 3 material variants: Bio1, Bio5 or PP

520: With a width of 520 cm pulled apart, the largest possible area is obtained

C20: Due to the cut length of 20 cm, the mesh size Ø is approx. 13 cm, net area approx. 85 m²,
(with C14 the cut length is 14 cm, the mesh size Ø approx. 9 cm, the net area approx. 75 m²)
C20 is standard, C14 is for slope greening.

/6: Thickness approx. 6 mm. For C20 there are 6, for C14 there are 4- or 6-mm variants.

2.1 LITE-NET Standard roll Bio1 C 20/6:

Net-shaped water storage nonwoven as vegetation aid, installed underground for conducting, distributing and temporarily storing water and air at the root level, cut from 100 % **biodegradable** wood-based cellulose needle nonwoven (approx. 600 g/m², thickness approx. 6 mm, pore content/water storage ≥ 85 %, **degradation time approx. 1-2 years**). Rootable drainage net with mesh size Ø approx. 13 cm, can be pulled apart to at least 5 times its width.

Delivery form:

- Bio1 175 C20/6: Net area max. 28 m²** (or **3 pcs. á 28m²**) with appr. 1,75 x 16,3 m. roll with width appr. 0,4 m, length appr. 20 m, Ø ca. 0,35 m, weight appr. 4,8 kg.
- Bio1 350 C20/6: Net area max. 57 m²** with appr. 3,5 x 16,3 m. roll with width appr. 0,8 m, length appr. 20 m, Ø ca. 0,35 m, weight appr. 9,6 kg.
- Bio1 520 C20/6: Net area max. 85 m²** with appr. 5,2 x 16,3 m. roll with width appr. 1,2 m, length appr. 20 m, Ø ca. 0,35 m, weight appr. 14,4 kg.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

2.2 LITE-NET Standard roll Bio5 C20/6:

Net-shaped water storage nonwoven as vegetation aid, installed underground for conducting, distributing and temporarily storing water and air at the root level, cut from 100 %

biodegradable/compostable PLA needle nonwoven (approx. 70 % PLA + 30 % cellulose, approx. **500 g/m²**, thickness approx. **6 mm**, pore content/water storage $\geq$ 85 %, **degradation time approx. 5-10 years**). Rootable drainage net with mesh size $\varnothing$ approx. 13 cm, can be pulled apart to at least 5 times the width.

Delivery form:

- Bio5 175 C20/6: Net area max. 28 m²** (or **3 pcs. á 28m²**) with appr. 1,75 x 16,3 m. roll with width appr. 0,4 m, length appr. 20 m, $\varnothing$ ca. 0,35 m, weight appr. 4,0 kg.
- Bio5 350 C20/6: Net area max. 57 m²** with appr. 3,5 x 16,3 m. roll with width appr. 0,8 m, length appr. 20 m, $\varnothing$ ca. 0,35 m, weight appr. 8 kg.
- Bio5 520 C20/6: Net area max. 85 m²** with appr. 5,2 x 16,3 m. roll with width appr. 1,2 m, length appr. 20 m, $\varnothing$ ca. 0,35 m, weight appr. 12 kg.

2.3 LITE-NET Standard roll PP C20/5:

Net-shaped water storage nonwoven as a **permanent** vegetation aid, installed underground for conducting, distributing and temporarily storing water and air at the root level, cut from PP - needle nonwoven (approx. **600 g/m²**, UV stabilized, thickness approx. **5 mm**, pore content/water storage $\geq$ 85%, pore opening width $< 80 \mu\text{m}$ (EN ISO 12956), maximum tensile force $\geq 40 \text{ kN/m}$ (EN ISO 10319)). Rootable drainage net with **mesh size $\varnothing$ approx. 13 cm**, can be pulled apart to at least 5 times the width.

Delivery form:

- PP 175 C20/5: Net area max. 28 m²** (or **3 pcs. á 28m²**) with appr. 1,75 x 16,3 m. roll with width appr. 0,4 m, length appr. 20 m, $\varnothing$ ca. 0,35 m, weight appr. 4,8 kg.
- PP 350 C20/5: Net area max. 57 m²** with appr. 3,5 x 16,3 m. roll with width appr. 0,8 m, length appr. 20 m, $\varnothing$ ca. 0,35 m, weight appr. 9,6 kg.
- PP 520 C20/5: Net area max. 85 m²** with appr. 5,2 x 16,3 m. roll with width appr. 1,2 m, length appr. 20 m, $\varnothing$ ca. 0,35 m, weight appr. 14,4 kg.
- PP 520 X20/5 XL: Net area max. 275 m²**, appr. 5.2 x 52.9 m. Roll with a width of appr. 1.2 m, length appr. 65 m, diameter appr. 0.35 m, weight appr. 14.4 kg.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

2.5 LITE-NET Slope:

Above-ground water storage and erosion protection as a vegetation aid in 2 sizes, 2 materials and 2 thicknesses



2.5.1 LITE-NET slope roll Bio1 C14/4:

Net-shaped water storage nonwoven as a vegetation aid and erosion protection for slopes, laid above ground to collect and store rainwater, cut from 100 % **biodegradable** wood-based cellulose needle nonwoven (approx. 330 g/m², **thickness approx. 4 mm**, pore content/water storage ≥ 85 %, **degradation time approx. 1-2 years**). Rootable drainage net with mesh size Ø approx. 9 cm, can be pulled apart to at least 5 times its width. Ideal in combination with spray greening.

Delivery form:

- a. **Bio1 350 C14/4: Net area max. 50 m²** with appr. 3,5 x 14,3 m.
roll with width appr. 0,8 m, length appr. 20 m, Ø ca. 0,35 m, weight appr. 5,3 kg.
- b. **Bio1 520 C14/4: Net area max. 75 m²** with appr. 5,2 x 14,3 m.
roll with width appr. 1,2 m, length appr. 20 m, Ø appr. 0,35 m, weight appr. 7,9 kg.

2.5.2 LITE-NET slope roll Bio1 C14/6:

Net-shaped water storage nonwoven as a vegetation aid and erosion protection for slopes, laid above ground to collect and store rainwater, cut from 100 % **biodegradable** wood-based cellulose needle nonwoven (approx. 600 g/m², **thickness approx. 6 mm**, pore content/water storage ≥ 85 %, **degradation time approx. 1-2 years**). Rootable drainage net with mesh size Ø approx. 9 cm, can be pulled apart to at least 5 times its width. Ideal in combination with spray planting.

Delivery form:

- a. **Bio1 350 C14/6: Net area max. 50 m²** with appr. 3,5 x 14,3 m.
roll with width appr. 0,8 m, length appr. 20 m, Ø appr. 0,35 m, weight appr. 9,6 kg.
- b. **Bio1 520 C14/6: Net area max. 75 m²** with appr. 5,2 x 14,3 m.
roll with width appr. 1,2 m, length appr. 20 m, Ø appr. 0,35 m, weight appr. 14,4 kg

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

2.5.3 LITE-NET slope roll Bio5 C14/6:

Net-shaped water storage nonwoven as a vegetation aid and erosion protection for slopes, laid above ground to collect and store rainwater, cut from 100 % **biodegradable/compostable** PLA needle nonwoven (approx. 70 % PLA + 30 % cellulose, approx. 500 g/m², **thickness approx. 6 mm**, pore content/water storage ≥ 85 %, **degradation time approx. 5-10 years**). Rootable drainage net with mesh size Ø approx. 9 cm, can be pulled apart to at least 5 times its width. Ideal in combination with spray greening.

Delivery form:

- a. **Bio5 350 C14/6: Net area max. 50 m²** with appr. 3,5 x 14,3 m.
roll with width appr. 0,8 m, length appr. 20 m, Ø ca. 0,35 m, weight appr. 8 kg.
- b. **Bio5 520 C14/6: Net area max. 75 m²** with appr. 5,2 x 14,3 m.
roll with width appr. 1,2 m, length appr. 20 m, Ø ca. 0,35 m, weight appr. 12 kg.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

3. LITE-NET tree:

Pre-assembled vegetation and distribution nets for tree new plantings in 2 sizes* and 3 materials for wrapping around root balls and/or for horizontal laying under the root ball:



Bio1



Bio5



PP

3.1 LITE-NET tree Bio1:

Ready-made drainage net for large-scale underground water and air supply of root balls, cut from 100 % **biodegradable** wood-based cellulose needle nonwoven (approx. 600 g/m², thickness approx. 6 mm, pore content/water storage ≥ 85 %, **degradation time approx. 1-2 years**).

Delivery form:

- LITE-NET tree Bio1 L (90, 20 or 6 x 3 pcs): Rootable nonwoven net with mesh size appr. Ø 10 cm for the wrapping of **root balls Ø up to max. 60/65 cm**, size max. 1,2 m² with appr. 1,5 x 0,8 m.
- LITE-NET tree Bio1 XL (45 pcs): Rootable nonwoven net with mesh size appr. Ø 13 cm for the wrapping of **root balls Ø = from approx. 60 cm**, size max. 2,8 m² with appr. 1,75 x 1,6 m.

3.2 LITE-NET tree Bio5:

Ready-made drainage net for large-scale underground water and air supply of root balls, cut from 100 % **biodegradable/compostable** PLA needle nonwoven (approx. 70% PLA + 30 % cellulose, approx. 500 g/m², thickness approx. 6 mm, pore content/water storage ≥ 85%, **degradation time approx. 5-10 years**).

Delivery form:

- LITE-NET tree Bio5 L (90, 20 or 6 x 3 pcs): Rootable nonwoven net with mesh size appr. Ø 10 cm for the wrapping of **root balls Ø up to max. 60/65 cm**, size max. 1,2 m² with appr. 1,5 x 0,8 m.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

- b. LITE-NET tree Bio5 XL (45, 8, 4 x 2 pcs): Rootable nonwoven net with mesh size appr. Ø 13 cm for the wrapping of **root balls Ø = from approx. 60 cm**, size max. 2,8 m² with appr. 1,75 x 1,6 m.

3.3 LITE-NET tree PP:

Ready-made drainage net for large-scale underground water and air supply of root balls, cut from durable PP needle nonwoven (approx. 600 g/m², UV stabilized, thickness approx. 5 mm, pore content/water storage ≥ 85%, pore opening width < 80 µm (EN ISO 12956), maximum tensile force ≥ 40 kN/m (EN ISO 10319)).

Delivery form:

- a. LITE-NET tree PP L (90, 20 or 6 x 3 pcs): Rootable nonwoven net with mesh size appr. Ø 10 cm for the wrapping of **root balls Ø up to max. 60/65 cm**, size max. 1,2 m² with appr. 1,5 x 0,8 m.
- b. LITE-NET tree PP XL (45, 8, 4 x 2 pcs): Rootable nonwoven net with mesh size appr. Ø 13 cm for the wrapping of **root balls Ø = from approx. 60 cm**, size max. 2,8 m² with appr. 1,75 x 1,6 m.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

4. LITE-ROOTPROTECT Root protection nonwoven for construction sites:

4.1 root curtain:

Full-surface nonwoven as biodegradable construction site protection with water storage function in 2 widths:

Root curtain, 330 g/m²:

100 % **biodegradable** water storage and protection nonwoven for root curtains (pore content > 85 %, fiber thickness < 2 dtex, weight appr. 330 g/m², thickness min. 3.5 mm, maximum tensile strength lengthwise/crosswise > 190 N/5 (DIN EN 29073-3)). 100 % cellulose needle nonwoven without chemical additives.

Nonwoven can simply be poured over at the end of the construction site and supports irrigation and deep aeration for **approx. 1-2 years**.

On request with center/edge flap for inserting irrigation tubes.

Delivery form:

- a. **Root curtain M:** roll with 80 cm width and 20 m length
- b. **Root curtain L:** roll with 120 cm width and 20 m length

4.2 root bandage:



Nonwoven roll as biodegradable construction site protection with water storage function:

Root bandage 330 g/m²:

100 % **biodegradable** root bandage to protect exposed roots at construction sites.

Water storage needle nonwoven made of 100 % cellulose without chemical additives for moisture retention as well as mechanical and UV protection. Pore content > 85%, fiber thickness < 2 dtex, weight appr. 330 g/m², thickness min. 3.5 mm, maximum tensile strength lengthwise/crosswise > 190 N/5 (DIN EN 29073-3).

Nonwoven can simply be poured over at the end of the construction site. **Degradation time approx. 1-2 years**

Delivery form: 8 pieces rolls with width 10 cm and length 8 m
16 pieces rolls with width 10 cm and length 8 m

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

5. BLUELITE-NET:

For **water-saving underground** irrigation of lawns, athletic fields, golf courses, green roofs, slopes, etc.

(system consisting of 2 components, a distribution net and a nonwoven-covered drip tube laid on top of it):



5.1 LITE-NET Standard roll PP (component 1):

+

5.2 BLUELITE-TUBE (component 2):

Geotextile-wrapped drip irrigation pipe comprising:

a. Rivulis D5000 PCAS hose, 16 mm (13.8 mm inner Ø, 15.83 mm outer Ø), operating pressure 0.5–3.5 bar, wall thickness 40 mil (1.02 mm), emitter spacing 30 cm, flow rate 1.5 l/h, required filtration: 120 mesh, maximum lateral length 163 m at 3.5 bar.

b. Rain Bird XFD hose, 16 mm (13.6 mm inner Ø, 16.1 mm outer Ø), wall thickness 1.2 mm (49 mil), operating pressure 1.38–4.14 bar, flow rate 1.6 l/h, required filtration: 120 mesh, water temperature up to 37.8 °C, ambient temperature up to 51.7 °C, maximum lateral length 175 m at 4.14 bar (max. 32 m at 1.4 bar, max. 112 m at 2.1 bar).

c. Rain Bird XFS hose, 16 mm (13.6 mm inner Ø, 16.1 mm outer Ø), wall thickness 1.2 mm (49 mil), operating pressure 1.38–4.14 bar, flow rate 1.6 l/h, required filtration: 120 mesh, water temperature up to 37.8 °C, ambient temperature up to 51.7 °C, maximum lateral length 175 m at 4.14 bar (max. 32 m at 1.4 bar, max. 112 m at 2.1 bar).

Protective sleeve with water distribution function made of durable PP needle-punched nonwoven fabric (approx. 360 g/m², UV-stabilized, thickness approx. 3.3 mm, pore opening size < 90 µm (EN ISO 12956)), tensile strength ≥ 25 kN/m (EN ISO 10319), width approx. 5 cm, for installation on LITE-NET drainage geotextile mesh at a spacing of approx. 50–60 cm (fastening with ground staples if required).

Roll length: approx. 100 m.

Supply format: 55, 85 or 1200 m².

or

5.3 BLUELITE-COVER (component 2, without drip irrigation tube):

Protective and distribution nonwoven cover for drip irrigation pipes, made of durable PP needle

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

All in ONE: Air-Soil-Water

nonwoven (approx. 360 g/m², UV stabilized, thickness approx. 3.3 mm, pore opening width < 90 µm (EN ISO 12956)), maximum tensile force ≥ 25 kN/m (EN ISO 10319), width approx. 6 cm, for insertion of own or individual irrigation tubes for laying on LITE-NET drainage nonwoven net with spacing approx. 50 -60 cm (if required, fastening by means of plug-in bracket).

Roll length appr. 25 m.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

6. LITE-CUBES:

Extra-small water storage cubes for long-term irrigation and aerification as well as for mixing into the spray irrigation slurry, in 3 material variants:



Bio1



Bio5



PP

6.1. LITE-CUBES Bio1:

Water storage nonwoven in cube form (approx. 12/12/6 mm) cut from 100 % **biodegradable** wood-based cellulose needle nonwoven (approx. 600 g/m², thickness approx. 6 mm, pore ratio/water storage ≥ 85 %, water storage capacity approx. up to 10 l/kg, **degradation time approx. 1-2 years**) for mixing into the substrate for growing pots or for spray planting. Mixing ratio of approx. 5-10 % by volume for growing pots.

Delivery form: 250l or 1000l (appr. 60 kg)

6.2 LITE-CUBES Bio5:

Water storage nonwoven in cube form (approx. 12/12/6 mm), cut from 100 % **biodegradable/compostable** PLA needle nonwoven (approx. 70% PLA + 30 % cellulose, approx. 500 g/m², thickness approx. 6 mm, pore content/water storage ≥ 85%, water storage capacity approx. up to 10 l/kg, **degradation time approx. 5-10 years**) for sweeping into aerification holes, e.g. on golf courses or into slot drains on lawns.

Delivery form: 250l or 1000l (appr. 55 kg)

6.3 LITE-CUBES PP:

Water storage nonwoven in cube form (approx. 12/12/5 mm), cut from **durable**, reusable PP needle-punched nonwoven (approx. 600 g/m², UV stabilized, thickness approx. 5 mm, pore content ≥ 85%, pore opening width < 65 µm (EN ISO 12956), water storage capacity approx. up to 10 l/kg). Mixing ratio of approx. 5-10 % by volume for green roofs.

Delivery form: 250l or 1000l (appr. 60 kg)

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

7. BLUELITE-RING:

For effective, uniform, protected and long-term underground irrigation.

For new plantings in combination with LITE-NET tree.



7.1 BLUELITE-RING: Ready-made for trees

BLUELITE-RING: Nonwoven-covered irrigation tube (3 outlet openings per m, appr.2l water per opening/h, tube diameter 16 mm) with water distribution function made of durable PP needle nonwoven (appr.360 g/m², UV stabilized, thickness appr.3.3 mm, pore opening width < 90 µm (EN ISO 12956)), maximum tensile force ≥ 25 kN/m (EN ISO 10319), width appr.6 cm, for covered laying around a tree trunk. **Ring diameter approx. 50 cm.**

Sales unit: 10 pcs.

7.2 BLUELITE-TUBE and BLUELITE-COVER: Long rolls for individual cutting for new tree planting, with and without irrigation tube:

BLUELITE-TUBE:

Nonwoven-covered irrigation tube (Rivulis D5000 PCAS hose with 16 mm (13.8 / 15.83 mm), 0.5 - 3.5 bar, 40 mil (1.02 mm), 1.5 l/h, 30 cm dripper distance) with water distribution function made of durable PP needle nonwoven (appr.360 g/m², UV stabilized, thickness appr.3.3 mm, pore opening width < 90 µm (EN ISO 12956)), maximum tensile force ≥ 25 kN/m (EN ISO 10319), width appr.6 cm, for covered laying around or along trees.

Roll length: 100 m.

BLUELITE-COVER:

Protective and distribution cover made of durable PP needle fleece (approx. 360 g/m², UV-stabilised, thickness approx. 3.3 mm, pore size < 90 µm (EN ISO 12956)), maximum tensile strength ≥ 25 kN/m (EN ISO 10319), width approx. 6 cm, for inserting your own or individual irrigation pipes and then laying them covered around or along trees.

Roll length: 25 m.

Delivery form: 16 pcs. á 25 m.

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

ALL in ONE: Air-Soil-Water

8. SALFIX-MAT:

THE FILTER MAT FOR PROTECTION AGAINST DE-ICING SALT:



8.1 SALFIX-MAT:

The 3-layer **SALFIX-MAT** consists of an ion-exchange mixture enclosed between two robust filter fleeces. The salt is separated from the water and chemically bound within the AquaTextile. If salt-contaminated water flows in from the side, the edge can be folded over by 20–30 cm, creating a double layer at the exposed edge with higher buffer capacity.

Filter mat made of durable PP needle fleece and ion-exchange mixture (total approx. 4 kg/m², UV-stabilized, thickness approx. 8 mm, pore opening size < 90 µm (EN ISO 12956)), maximum tensile strength ≥ 25 kN/m (EN ISO 10319).

A tree pit covered with 4 m² of salt filter mats can— in addition to mechanically filtered salt— chemically bind up to approx. 1 kg of salt, depending on the conditions.

Of this, about 0.9 kg is permanently fixed, and an additional approx. 0.2 kg of salt can be gently washed out by pure water— harmless for plants— thereby restoring absorption capacity for the next winter season, ensuring the mat's long-term effectiveness. The mat serves as both a filter and a protective layer and is UV-stabilized; however, for long-term use, it should be covered with a water-permeable layer, such as gravel or a grating.

The innovative **SALFIX-MAT**, a water-permeable filter mat, provides long-term binding of de-icing salt, thus preventing tree damage and soil compaction. Trees survive the winter sustainably, avoiding costly replanting. The installation is simple: place one mat on each side of the trunk within the tree pit, creating a filter area of either 2.0 × 2.0 m or 3.0 × 3.0 m.

Delivery form:

- 4 m² – 2 pieces, each 2 × 1 m
- 9 m² – 2 pieces, each 3 × 1.5 m

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request





LITE-SOIL

All in ONE: Air-Soil-Water

PRODUCT RECOMMENDATIONS:

	TREES				SLOPES			ATHLETIC FIELDS & LAWNS			FRUIT & VITI- CULTURE		GREEN ROOFS		RAISED PLANTING BEDS & TROUGH PLANTERS		
	GROWING	LONG-TERM	IRRIGATION	LARGE TREE- TRANSPLANTATION	GROWING	LONG-TERM	IRRIGATION	GROWING	LONG-TERM	IRRIGATION	LONG-TERM	IRRIGATION	LONG-TERM	IRRIGATION	1 YEAR	LONG-TERM	IRRIGATION
LITE-STRIPS																	
Bio1	•				•			•							•		
Bio5	•	•	•		•	•		•	•		•					•	•
PP		•	•			•	•		•	•	•	•	•	•		•	•
LITE-NET TREE																	
Bio1	•			•											•		
Bio5	•	•	•	•							•					•	•
PP		•	•	•							•					•	•
LITE-NET C14																	
Bio1					•										•		
Bio5					•	•			•							•	
LITE-NET C20																	
Bio1	•			•											•		
Bio5																•	•
PP		•	•	•		•	•		•	•	•	•	•	•		•	•
BLUELITE-NET																	
COVER			•				•			•		•		•			•
TUBE			•				•			•		•		•			•
RING			•									•					•

Lite-Soil GmbH | Neustiftgasse 94/23, A-1070 Vienna | +43 1 5227310 | office@lite-soil.com | www.lite-soil.com

Status July 2026, other sizes and materials on request

